

YORK GOLD

Sanding Bands

Zirconium SB, X-weight backing. Ensures quick and highly efficient stock removal. It's recommended for applications such as finishing of moulded parts, internal surfaces of cylinders, pipes and drilled parts in general. For use on standard steel and stainless steel surfaces.



Diameter x Width (mm)	Grit*	Max. (rpm)	Order Code YRK-205
10 x 10	P80	38,000	-3782A
	P120	38,000	-3782B
	P50	38,000	-3782C
10 x 20	P60	38,000	-3782D
	P80	38,000	-3782E
	P120	38,000	-3782F
13 x 25	P36	30,000	-3782G
	P50	30,000	-3782H
	P60	30,000	-3782J
15 x 10	P80	30,000	-3782K
	P120	30,000	-3782L
15 x 30	P60	26,000	-3782M
	P80	26,000	-3782N
19 x 25	P36	26,000	-3782P
	P50	26,000	-3782Q
	P60	26,000	-3782R
22 x 20	P80	26,000	-3782S
	P120	26,000	-3782T
25 x 25	P36	20,000	-3782V
	P50	20,000	-3782W
	P60	20,000	-3782X
30 x 20	P80	20,000	-3782Y
	P120	20,000	-3782Z
30 x 30	P36	17,000	-3783A
	P50	17,000	-3783B
	P60	17,000	-3783C
38 x 25	P80	17,000	-3783D
	P36	15,000	-3783E
	P50	15,000	-3783F
45 x 30	P60	15,000	-3783G
	P80	15,000	-3783H
	P120	15,000	-3783J
51 x 25	P36	13,000	-3783K
	P50	13,000	-3783L
	P60	13,000	-3783M
60 x 30	P80	13,000	-3783N
	P120	13,000	-3783P
75 x 30	P36	13,000	-3783Q
	P50	13,000	-3783R
	P60	13,000	-3783S
100 x 40	P80	13,000	-3783T
	P120	13,000	-3783V
100 x 40	P36	10,000	-3783W
	P50	10,000	-3783X
	P60	10,000	-3783Y
100 x 40	P80	10,000	-3783Z
	P120	10,000	-3784A
100 x 40	P36	8,500	-3784B
	P50	8,500	-3784C
	P60	8,500	-3784D
100 x 40	P80	8,500	-3784E
	P120	8,500	-3784F
100 x 40	P36	7,500	-3784G
	P50	7,500	-3784H
	P60	7,500	-3784J
100 x 40	P80	7,500	-3784K
	P120	7,500	-3784L
100 x 40	P36	6,500	-3784M
	P50	6,500	-3784N
	P60	6,500	-3784P
100 x 40	P80	6,500	-3784Q
	P120	6,500	-3784R
100 x 40	P36	5,000	-3784S
	P50	5,000	-3784T
	P60	5,000	-3784V
100 x 40	P80	5,000	-3784W
	P120	5,000	-3784X
100 x 40	P36	4,000	-3784Y
	P50	4,000	-3784Z
	P60	4,000	-3784W

YORK ABRASIVES

Sanding Bands

Spiral wound with tear-resistant backing fabric. For grinding and finishing edges, profiles, welded joints etc. For use with power tools. Aluminium Oxide for use on most metals.



Diameter x Width (mm)	Grit*	Max. (rpm)	Order Code YRK-205
10 x 10	P60	38,000	-0520K
	P80	38,000	-0550K
	P150	38,000	-0580K
10 x 20	P60	38,000	-0720K
	P80	38,000	-0750K
	P150	38,000	-0780K
13 x 10	P60	30,000	-0920K
	P80	30,000	-0950K
	P150	30,000	-0980K
13 x 25	P60	30,000	-1120K
	P80	30,000	-1150K
	P150	30,000	-1180K
15 x 10	P60	26,000	-1320K
	P80	26,000	-1350K
	P150	26,000	-1380K
15 x 30	P60	26,000	-1520K
	P80	26,000	-1550K
	P150	26,000	-1580K
19 x 25	P60	20,000	-1720K
	P80	20,000	-1750K
	P150	20,000	-1780K
22 x 20	P60	17,000	-1920K
	P80	17,000	-1950K
	P150	17,000	-1980K
25 x 25	P60	15,000	-2120K
	P80	15,000	-2150K
	P150	15,000	-2180K
30 x 20	P60	13,000	-2320K
	P80	13,000	-2350K
	P150	13,000	-2380K
30 x 30	P60	13,000	-2520K
	P80	13,000	-2550K
	P150	13,000	-2580K
38 x 25	P60	10,000	-2720K
	P80	10,000	-2750K
	P150	10,000	-2780K
45 x 30	P60	8,500	-2920K
	P80	8,500	-2950K
	P150	8,500	-2980K
51 x 25	P60	7,500	-3120K
	P80	7,500	-3150K
	P150	7,500	-3180K
60 x 30	P60	6,500	-3320K
	P80	6,500	-3350K
	P150	6,500	-3380K
75 x 30	P60	5,000	-3520K
	P80	5,000	-3550K
	P150	5,000	-3580K
100 x 40	P60	4,000	-3720K
	P80	4,000	-3750K
	P150	4,000	-3780K

Sanding Band Kits

21 Piece Kits

Spiral wound with tear-resistant backing fabric. For grinding and finishing edges, profiles, welded joints etc. For use with power tools.

Aluminium oxide for use on most metals.

21
PIECES



Size (mm)	Contents	Order Code YRK-205
15 x 30	10 x P60	-9360K
	6 x P80	
	4 x P150	
	1 x 6mm Shank Holder	
25 x 25	10 x P60	-9320K
	6 x P80	
	4 x P150	
	1 x 6mm Shank Holder	
51 x 25	10 x P60	-9340K
	6 x P80	
	4 x P150	
	1 x 6mm Shank Holder	

Drum Holders

Suitable for use with chucks/collets on all portable power and air tools. Self expanding when in use for a secure grip on abrasive sanding bands. All shanks are 6mm, except where marked * which has an 8mm shank.



Diameter x Width (mm)	Weight per 5	Order Code YRK-205
10 x 10	50g	-4100K
10 x 20	70g	-4130K
13 x 25	80g	-4190K
15 x 10	70g	-4220K
15 x 30	100g	-4250K
19 x 25	110g	-4280K
22 x 20	120g	-4310K
25 x 25	140g	-4340K
30 x 20	150g	-4370K
30 x 30	200g	-4400K
38 x 25	240g	-4430K
45 x 30	380g	-4460K
51 x 25	360g	-4490K
60 x 30	460g	-4520K
75 x 30*	1100g	-4550K

Fitting/Removal Of Bands

Spindle Rotation
During Use

(Holder expands)

Band
Rotation

(Holder stationary)



Max Operating Speeds (Peripheral=25M/sec)

Band Dia. (mm)	Max. (rpm)	Band Dia. (mm)	Max. (rpm)
10	47,500	30	15,800
13	36,500	38	12,500
15	31,500	45	10,500
19	25,000	51	9,300
22	21,500	60	7,900
25	19,000	75	6,300
		100	4,700