Produces burr free cuts without distortion. Ideal for body shop and sheet metal work, teasing throttle for precise control, V<sub>4</sub>" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm\* air consumption and a cutting capacity of 1.6mm (steel) to 2.0mm (aluminium).

Sound pressure level: 91dBA. Sound power



\*Based on a 15 second cycle per minute average use.

| Cutting Rate | Weight | Order Code |
|--------------|--------|------------|
| Per Min.     | each   | KBE-270    |
| 2.6m         | 900g   | -3400K     |

# Punches & Dies for Nibblers

Produce burr free cuts without distortion. Ideal for body shop and sheet metal work. Suitable for use with Kobe NB160 high performance

nibbler. KBE-298 parts cut on upstroke. KBE-280 parts cut on downstroke.



Newer

NB160



|         | ·                                 |         |
|---------|-----------------------------------|---------|
| KBE-298 |                                   | KBE-280 |
|         | Weight Order Code<br>each KBE-298 |         |

-5003C

Upstroke

Type

Punch

Die

| Downstr      | oke              |                |                       |  |
|--------------|------------------|----------------|-----------------------|--|
| Type         | To Suit<br>Model | Weight<br>each | Order Code<br>KBE-280 |  |
| Punch<br>Die | Older<br>NB160   | 5g<br>75g      | -0025A<br>-0028A      |  |

75g

# **Rapid Cutting Metal Shear**

# SH120

Produces burr-free cuts without distortion. Ideal for body shop and sheet metal work. Teasing throttle for precise control, 1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm\* air consumption, cutting capacity of 1.2mm steel to 1.6mm aluminium.



\*Based on a 15 second cycle per minute average use.

| Strokes  | Weight | Order Code |
|----------|--------|------------|
| Per Min. | each   | KBE-270    |
| 2,200    | 2.30kg | -3900K     |

# Shear Head

Produces burr free cuts without distortion. Ideal for body shop and sheet metal work. Suitable for use with Kobe SH120 rapid cutting metal shear.

| To Suit | Weight | Order Code |
|---------|--------|------------|
| Model   | each   | KBE-280    |
| SH120   | 360g   |            |



HEAVY DUTY

## Multi-Purpose Body Saw RS9201

Produces burr free cuts without distortion. Ideal for body shop and sheet metal work. Teasing throttle for precise control, 1/4" NPT air

inlet thread, 90psi air pressure, 4cfm\* air consumption and a cutting capacity of 1.6mm (steel) to 2mm (aluminium).

Sound pressure level: 91dBA. Sound power level: 102dBA. Vibration level: 5.1m/s².

Overall length: 235mm.

| Free Speed | Weight | Order Code |  |
|------------|--------|------------|--|
| (rpm)      | each   | KBE-270    |  |
| 9,000      | 550g   | -3500K     |  |

\*Based on a 15 second cycle per minute average use.

## Accepts most square-ended blades up to 1mm thick x 12mm wide

| Туре              | Teeth<br>Per Inch | Pack<br>Quantity | Order Code<br>KBE-280 |  |
|-------------------|-------------------|------------------|-----------------------|--|
| All Hard -        | 24                | 2                | -5670K                |  |
| For Straight Cuts | 32                | 2                | -5672K                |  |
| Bi-Metal -        | 24                | 2                | -5674K                |  |
| For Curved Cuts   | 32                | 2                | -5676K                |  |

# Shatter Resistant Body Saw Blades

HSS body saw blade with two tooth pitch variations. 24 tooth (medium) and 32 tooth (fine) to suit a wide range of applications. Sold in packs of two.

# Hammer & Chisel Kit

# HP2090K

Supplied with flat chisel, spot weld breaker, taper punch, rivet cutter and sheet metal cutter. Hard hitting long stroke. Accepts all standard 0.401" shank tools, 74" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm\* air consumption.

Stroke length: 90mm. Sound pressure level: 105dBA. Sound power level: 118dBA. Vibration level: 11.5m/s<sup>2</sup>.

Overall length: 230mm.



| Free Speed | Weight | Order Code | *Based on a         |
|------------|--------|------------|---------------------|
| (rpm)      | each   | KBE-270    | 15 second cycle per |
| 2,000      | 3.00kg | -3100K     | minute average use. |

# **Heavy Duty Needle Scaler** NS4030

10 needles for quick removal of rust, paint, scale, flux and corrosion. Slimline body. Lightweight. (For replacement scaling needles, please refer to parts drawing supplied with tool), 1/4" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm\* air consumption.

Needle diameter: 3mm. Sound pressure level: 95dBA. Sound power level: 109dBA. Vibration level: 12.8m/s<sup>2</sup>.



\*Based on a 15 second cycle per minute average use.

Scaler Needles for use with Kobe Needle Scaler NS4030



| Number of<br>Needles |        |
|----------------------|--------|
| Set 10               | -0019A |

DUTY

# Heavy Duty **Pistol Grip Hammer**

For a wide range of workshop and automotive uses. Supplied with retainer spring. Accepts all standard 0.401" shank tools, 1/4" NPT air inlet thread for 10mm air hose. 90psi air pressure, 4cfm\* air consumption.

Stroke length: 90mm. Sound pressure level: 109dBA. Sound power level: 119dBA. Vibration level: 11.2m/s<sup>2</sup>. Overall length: 225mm.



\*Based on a 15 second cycle per minute average use.

AVAILABLE



# Pistol Grip Hammer

Weight each

2.00kg

Order Code KBE-270

-3050K

## HP4540

Blows Per

Minute

2,100

Suitable for use with cutters, punches, spot weld breakers and flat chisels. Supplied with retainer spring. Accepts all standard 0.401" shank tools, V4" NPT air inlet thread for 10mm air hose, 90psi air

pressure, 4cfm\* air consumption.

Stroke length: 40mm.

|       | l pressure level: 112dBA.<br>I power level: 121dBA. |
|-------|---|
|       | tion level: 15,5m/s².                               |
| Overo | ıll length: 145mm.                                  |
|       |   |
|       |   |

| Blows Per | Weight | Order Code |
|-----------|--------|------------|
| Minute    | each   | KBE-270    |
| 4,500     | 1.40kg | -3000K     |

# 289

\*Based on a 15 second cycle per minute average use.

# Hammer & Chisel Kit HP5040K

Supplied with flat chisel, spot weld breaker, taper punch and rivet cutter. Variable power regulator. Accepts all standard 0.401" shank tools.

Va" NPT air inlet thread for 10mm air hose, 90psi air pressure, 4cfm\* air consumption.

Stroke length: 40mm.

| Sound pressure level: 112dBA. |
|-------------------------------|
| Sound power level: 119dBA.    |
| Vibration level: 14.8m/s².    |
| Overall length: 135mm.        |
|                               |
|                               |
|                               |

| Blows Per | Weight | Order Code |  |
|-----------|--------|------------|--|
| Minute    | each   | KBE-270    |  |
| 5,000     | 1.60kg | -3150K     |  |

\*Based on a 15 second cycle per minute average use.

# Retainers

Suitable for use with all Kobe air hammers.



| Retainer Type | Weight<br>each | Order Code<br>KBE-280 |
|---------------|----------------|-----------------------|
| Quick Change  | 60g            | -0001A                |
| Beehive       | 80g            | -0004A                |
| Zin Change    | 700            | -0007A                |

## Air Hammer Chucks

Suitable for use with all Kobe air hammers. Cannot accidentally be released.

# Safety Chuck

Spring loaded retainer, that must be unscrewed to allow tool release.



## Quick Change Chuck

Spring loaded front collar, that must be pulled forward to allow tool release.



| Chuck        | Weight | Order Code |  |
|--------------|--------|------------|--|
| Type         | each   | KBE-280    |  |
| Safety       | 70g    | -0010A     |  |
| Quick Change | 530g   | -0013A     |  |

# **Needle Scaler Attachment**

Converts a pneumatic hammer into a needle scaler.



| To Suit  | Weight<br>each | Order Code<br>KBE-280 |
|----------|----------------|-----------------------|
| All Kobe | 865g           | -0116A                |